

## Specification Sheet

# 14270



### DIMENSIONS:

Length (mm)	29 mm
Width – base flange (mm)	12 mm
Cord length (in)	30 inches

### INFORMATION REQUIRED BY EPA:

The level of noise entering a person's ear, when a hearing protector is worn as directed, is closely approximated by the difference between the A-weighted environmental noise level and the NRR.

Example:

1. The environmental noise level as measured at the ear is 92 dBA.
2. The NRR is 33 decibels (dB).
3. The level of noise entering the ear is approximately equal to [92 dB (A) -33] 59 dB (A).

**CAUTION:** For noise environments dominated by frequencies below 500 Hz the C-weighted environmental noise level should be used. Improper fit of this device will reduce its effectiveness in attenuating noise. Consult the enclosed instructions for proper fit. Although hearing protectors can be recommended for protection against the harmful effects of impulsive noise, the Noise Reduction Rating (NRR) is based on the attenuation of continuous noise and may not be an accurate indicator of the protection attainable against impulsive noise such as gunfire.

### PRODUCT DESCRIPTION:

DuraPlug™ uncorded reusable 3-layer flange earplug

- Unique 3-layer flange enhances sound insulated effect
- Firm stem for easy insertion and removal
- Washable and reusable
- Noise Reduction Rating (NRR): 25 dB
- Compliance with ANSI S3. 19-1974
- Each pair individually wrapped

### TECHNICAL DATA:

<b>Material:</b>	POLYMER
<b>Color:</b>	Red flange, yellow base
<b>Sizes:</b>	One size only
<b>Packaging:</b>	1 pair/polybag 100 polybags/box 10 boxes/case
<b>Registration Number (RN#):</b>	78713
<b>Country of Origin:</b>	Taiwan
<b>Harmonization Code (HTS#):</b>	3926.90.9980